

APPLICATION		REVISIONS			
NEXT ASSY	USED ON	LTR	DESCRIPTION	DATE	APPROVED
		A	REDRAWN WITH CHANGE ERR GSDT9287-K	97/09/30	CLD
		B	ERR GSD-U0463	98-01-09	DMA

1236902

NOTES:

1. APPLICABLE STANDARDS/SPECIFICATIONS:
 - A. DOD-STD-00100
 - B. ANSI Y14.5M - 1982
2. CLEAN AND TREAT OR COAT AS SPECIFIED ON DRAWING.
3. PRIME PER SPEC MIL-P-53030 OR MIL-P-53022.
DRY FILM THICKNESS .8-1.5 MILS MINIMUM.
4. TOPCOAT PER SPEC MIL-C-46168 OR MIL-C-53039, COLOR GREEN 383. DRY FILM THICKNESS 1.8 MILS MINIMUM.
5. PRETREATED SURFACES INCLUDE THOSE WHICH ARE ANODIZED, PLATED, OR PREVIOUSLY PAINTED.

PART NO. 12369021

PMIC A		CONTRACT NUMBER		U.S. ARMY TANK AUTOMOTIVE AND ARMAMENTS COMMAND WARREN, MICHIGAN 48397-5000	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: 2 PLACE 3 PLACE		CONTRACTOR		PAINT SYSTEMS FOR PRETREATED EXTERIOR SURFACES, GREEN 383	
MATERIAL		DRAWN BY KB	DATE (YR-MO-DA) 88-06-16	SIZE A	CAGE CODE 19207
		CHECKER HR	ENGINEER	12369021	
		DRAWING APPROVAL H. V. DEWOLF			
MATL ENGRG	QAP APPROVAL	DESIGN APPROVAL KREGG LEVESAITIN		SCALE NONE	UNIT WT. SHEET