

SPECIAL PACKAGING INSTRUCTION

Form Approved XABH
OMB No. 0704-0188

ABH

The public reporting burden for this collection of information is estimated to average 30 days per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THIS ADDRESS.

1. PART OR DRAWING NO. A001090555 24975 Alternating Generator		2. CAGE 19207	3. SPI NO. AK10729661
4. NATIONAL STOCK NO. 6115-01-072-9661		5. DATE 11/30/98	6. REVISION
7. QUP 1	8. ICQ NONE	9. UNIT PACK WT. 30.0	10. UNIT PACK CU 0.500
12. MILITARY PRESERVATION METHOD IA-14		18. STEPS	19. REQD
13. CLEANING MIL-P-116 PROCESS C-1		1B	20. DESCRIPTION PRESERVATIVE: MIL-C-16173, GR 1
14. DRYING MIL-P-116		2C	INTIMATE WRAP: MIL-B-121, TY II, GR A, CL 2
15. PACKING		3D	CUSHIONING: PPP-F-320, TY CF, CL DOM
a. LEVEL A MIL-STD-2073-1		4	CONTAINER: PPP-B-636, TY CF, CL DOM
b. LEVEL B MIL-STD-2073-1		5E	CLOSURE: A-A-883
16. MARKING MIL-STD-129		6F	BARRIER: MIL-B-117, ST 1, TY I, CL B
		7	CONTAINER: PPP-B-636, TY CF, CL WR
		8E	CLOSURE: PPP-T-60, TY III, CL 1

17. NOTES/DRAWING

A. QUALITY ASSURANCE PROVISIONS:
PRESERVATION AND PACKING SHALL BE INSPECTED IN ACCORDANCE WITH MIL-STD-2073.

1B. APPLY PRESERVATIVE TO UNPAINTED EXTERIOR METALLIC SURFACES.

2C. SINGLE WRAP REQUIRED. COMPUTE SIZE IN ACCORDANCE WITH MIL-STD-2073. SECURE WRAP WITH TAPE A-A-883.

3D. FIBERBOARD FILLER PADS AND / OR DIECUTS SHALL BE DEVISED AND USED TO IMMOBILIZE ITEM AND PREVENT DAMAGE TO ITEM OR CONTAINER.

4E. CONTAINER CLOSURE SHALL BE IN ACCORDANCE WITH THE CONTAINER SPECIFICATION.

5F. COMPUTE SIZE AND CONFORM BAG IN ACCORDANCE WITH MIL-STD-2073.

UNIT PACK WT, CU, AND SIZES ARE ESTIMATED AND ARE PROVIDED FOR INTERNAL GOVERNMENT PLANNING PURPOSES ONLY.

AK10729661