

NOTICE
OF CANCELLATION

INCH-POUND

MIL-R-3065E
NOTICE 2
21 January 2000

MILITARY SPECIFICATION

RUBBER, FABRICATED PRODUCTS

MIL-R-3065E, dated 16 May 1984, is hereby canceled. Future acquisition for this product should refer to ASTM D 2000, Standard Classification System for Rubber Products in Automotive Applications.

(ASTM D 2000 was DoD adopted on 25 February 1991, and is listed in the Department of Defense Index of Specifications and Standards (DoDISS) database. Applications for copies of ASTM publications should be addressed to the American Society of Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.)

Although it has been determined that ASTM D 2000 is a suitable replacement for MIL-R-3065E, users should evaluate this document for its particular application before citing it as a replacement document.

To obtain product dimension and tolerance requirements, users shall reference commercial specifications listed in the Rubber Manufacturer's Association (RMA) Rubber Handbook (A-3 commercial tolerances), and the RMA Rubber Sheet Packing Handbook. Other dimension and tolerance requirements shall be in accordance with the applicable part drawing or as indicated in the contract or purchase order. The RMA publications are available from the Rubber Manufacturer's Association, 1901 Pennsylvania Avenue, N.W., Washington, DC 20006.

MIL-R-3065E product references to MIL-STD-417 have been cross-referenced to ASTM D 2000 as follows (MIL-STD-417 was previously canceled):

<u>MIL-STD-417</u>	<u>ASTM D 2000</u>	<u>Type of polymer normally used</u>
RN	AA	Natural, synthetic/reclaimed rubbers
RS	AA,BA	Natural, synthetic/reclaimed rubbers
SA	AK,BK	Polysulfides
SB	BG	NBR polymers, urethane
SC	BC	Chloroprene polymers
TA	FC,FS,FE,GE	Silicones (high strength)
TB	DH	Polyacrylic polymers

MIL-R-3065E

Custodians:

Air Force - 99

Army - MR

Navy - SH

Preparing Activity:

DLA-GS

(Project 9320-0016)

Reviewers:

Air Force - 01, 11

Army - AL, AR, CR, GL, MI

Defense Threat Reduction Agency - DS

Navy - AS, OS, MC, YD2